



Castrol EDGE 10W-60

Fluid TITANIUM - Stronger Under Pressure

Description

Generating phenomenal amounts of horsepower, supercars are at the pinnacle of automotive engineering and performance. Continual advancement of supercar engines has led to extreme pressures – providing the ultimate test for engine oil. These intense pressures cause friction, which can waste up to 10% of an engine's performance.

Castrol EDGE SUPERCAR is proven in world-leading supercars and engineered with the most advanced technology for high-performance driving. Its patented Fluid TITANIUM transforms to be stronger under pressure and reduces friction for maximum engine performance when you need it most.

Suitable for use in everyday high-performance vehicles, Castrol EDGE SUPERCAR is proof that our oils are tested to the limits.

Castrol EDGE SUPERCAR with Fluid TITANIUM: unlock the true performance of your engine.

Application

Castrol EDGE 10W-60 is suitable for use in automotive gasoline and diesel vehicles where the manufacturer recommends: ACEA A3/B4, API SN/CF

Castrol EDGE 10W-60 is approved for use in vehicles from leading supercar manufacturers: Refer to Product Performance section.

Please refer to your owners handbook.

Advantages

Castrol EDGE 10W-60 with Fluid TITANIUM is the natural choice for drivers who demand maximum engine performance from supercars, sports cars, competition and latest technology, high powered engines. Operating under higher pressures, these engines require an oil with outstanding strength and performance.

Castrol EDGE 10W-60:

- Transforms to be strongest when the pressure is highest, protecting your engine
- Reduces power-robbing friction across engine speeds and conditions
- Independently tested at the highest standards for proven performance
- Recommended by world-leading car manufacturers
- Delivers low foam performance

Typical Characteristics

Name	Method	Units	Castrol EDGE 10W-60
Density @ 15C, Relative	ASTM D4052	g/ml	0.853
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	22.7
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	4879
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	160
Viscosity Index	ASTM D2270	None	173
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	203
Ash, Sulphated	ASTM D874	% wt	1.29

Product Performance Claims

ACEA A3/B3, A3/B4
API SN/CF
Approved for BMW M-Models
VW 501 01/ 505 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE 10W-60
05 Jul 2019
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

199 Oxford Road, Dunkeld, Johannesburg, 2196, South Africa
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)
www.castrol.co.za