

**Product Data Sheet** 

# Magna™ RD Range

Rock Drill Oils

# **Description**

Castrol Magna RD Range Oils (previously called Rock Drill™ Oils) consist of selected mineral oils specially compounded with lubricity fortifiers, corrosions inhibitors and tackiness additives.

### **Application**

Mining, quarrying, constructions, roadworks, tunneling and excavations.

Magna RD oils are recommended for the following well-known companies including Gardner-Denver, Atlas Copco and SIG.

However the correct grade should be selected against specific equipment and for local operating conditions. Most manufacturers include selection charts in their handbooks to assist in the selection of the correct grade.

### **Advantages**

Design features and benefits of the Castrol range of high quality rock drill oils include:

- High film strength.
- Reduced friction.
- Provide a suitable seal between piston and cylinder.
- · Reduced wear.
- Helps maintain maximum percussion efficiency.
- Preferentially adhere to metal surfaces and resist blow-off.
- Improved protection wear against wear caused by poor lubrication.
- Helps maintain operating speed.
- Reduced wear, allows operation in conditions of high or low temperatures.

# **Typical Characteristics**

Name	Method	Units	RD 46	RD 100	RD 150	RD 220	RD 320	RD 460
ISO Viscosity Grade	-	-	46	100	150	220	320	460
Density @ 15°C / 59°F	ASTM D4052 / ISO 12185	g/cm³	0.88	0.89	0.89	0.89	0.90	0.90
Kinematic Viscosity @ 40°C / 104°F	ASTM D445 / ISO 3104	mm²/	46	100	150	220	320	460
Kinematic Viscosity @ 100°C / 212°F	ASTM D445 / ISO 3104	mm²/	6.8	11.2	14.7	18.7	24.2	30.5
Pour Point	ASTM D97 / ISO 3016	°C/°F	-21 / -6	-18 / 0	-15 / 5	-15 / 5	-12 / 10	-9 / 16
Flash Point - open cup method	ASTM D92 / ISO 2592	°C/°F	220 / 428	230 / 446	240 / 464	260 / 500	255 / 491	255 / 491

Subject to usual manufacturing tolerances

This product was previously called Rock Drill. The name was changed in 2015.

Magna™ RD Range 29 Mar 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.